

[0039] For low pressure turbine radial compactness, there may be a relatively high ratio of radial span ($R_O - R_T$) to radius (R_O or R_T). Radial compactness may also be expressed in the hub-to-tip ratio (R_T/R_O). These may be measured at the maximum R_O location in the low pressure turbine section. The exemplary compact low pressure turbine section has a hub-to-tip ratio close to about 0.5 (e.g., about 0.4-0.5 or about 0.42-0.48, with an exemplary about 0.46).

[0040] Another characteristic of low pressure turbine radial compactness is relative to the fan size. An exemplary fan size measurement is the maximum tip radius R_{Tmax} of the fan blades. An exemplary ratio is the maximum R_O along the low pressure turbine section to R_{Tmax} of the fan blades. Exemplary values for this ratio are less than about 0.55 (e.g., about 0.35-0.55), more narrowly, less than about 0.50, or about 0.35-0.50.

[0041] To achieve compactness the designer may balance multiple physical phenomena to arrive at a system solution as defined by the low pressure turbine hub-to-tip ratio, the fan maximum tip radius to low pressure turbine maximum R_O ratio, the bypass area ratio, and the bypass area ratio to low pressure turbine airfoil count ratio. These concerns include, but are not limited to: a) aerodynamics within the low pressure turbine, b) low pressure turbine blade structural design, c) low pressure turbine disk structural design, and d) the shaft connecting the low pressure turbine to the low pressure compressor and speed reduction device between the low pressure compressor and fan. These physical phenomena may be balanced in order to achieve desirable performance, weight, and cost characteristics.

[0042] The addition of a speed reduction device between the fan and the low pressure compressor creates a larger design space because the speed of the low pressure turbine is decoupled from the fan. This design space provides great design variables and new constraints that limit feasibility of a design with respect to physical phenomena. For example the designer can independently change the speed and flow area of the low pressure turbine to achieve optimal aerodynamic parameters defined by flow coefficient (axial flow velocity/wheel speed) and work coefficient (wheel speed/square root of work). However, this introduces structural constraints with respect blade stresses, disk size, material selection, etc.

[0043] In some examples, the designer can choose to make low pressure turbine section disk bores much thicker relative to prior art turbine bores and the bores may be at a much smaller radius R_B . This increases the amount of mass at less than a "self sustaining radius". Another means is to choose disk materials of greater strength than prior art such as the use of wrought powdered metal disks to allow for extremely high centrifugal blade pulls associated with the compactness.

[0044] Another variable in achieving compactness is to increase the structural parameter AN^2 which is the annulus area of the exit of the low pressure turbine divided by the low pressure turbine rpm squared at its redline or maximum speed. Relative to prior art turbines, which are greatly constrained by fan blade tip mach number, a very wide range of AN^2 values can be selected and optimized while accommodating such constraints as cost or a countering, unfavorable trend in low pressure turbine section shaft dynamics. In selecting the turbine speed (and thereby selecting the transmission speed ratio, one has to be mindful that at too high a gear ratio the low pressure turbine section shaft (low shaft) will become dynamically unstable.

[0045] The higher the design speed, the higher the gear ratio will be and the more massive the disks will become and the stronger the low pressure turbine section disk and blade material will have to be. All of these parameters can be varied simultaneously to change the weight of the turbine, its efficiency, its manufacturing cost, the degree of difficulty in packaging the low pressure turbine section in the core cowl-ing and its durability. This is distinguished from a prior art direct drive configuration, where the high bypass area ratio can only be achieved by a large low pressure turbine section radius. Because that radius is so very large and, although the same variables (airfoil turning, disk size, blade materials, disk shape and materials, etc.) are theoretically available, as a practical matter economics and engine fuel burn considerations severely limit the designer's choice in these parameters.

[0046] Another characteristic of low pressure turbine section size is airfoil count (numerical count of all of the blades and vanes in the low pressure turbine). Airfoil metal angles can be selected such that airfoil count is low or extremely low relative to a direct drive turbine. In known prior art engines having bypass area ratio above 6.0 (e.g. 8.0-20), low pressure turbine sections involve ratios of airfoil count to bypass area ratio above 190.

[0047] With the full range of selection of parameters discussed above including, disk bore thickness, disk material, hub to tip ratio, and R_O/R_{Tmax} , the ratio of airfoil count to bypass area ratio may be below about 170 to as low as 10. (e.g., below about 150 or an exemplary about 10-170, more narrowly about 10-150). Further, in such embodiments the airfoil count may be below about 1700, or below about 1600.

[0048] One or more embodiments have been described. Nevertheless, it will be understood that various modifications may be made. For example, when reengineering from a baseline engine configuration, details of the baseline may influence details of any particular implementation. Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A turbofan engine comprising:

- an engine case;
- a gaspath through the engine case;
- a fan having a circumferential array of fan blades;
- a compressor in fluid communication with the fan;
- a combustor in fluid communication with the compressor;
- a turbine in fluid communication with the combustor, the turbine having a low pressure turbine section; and
- a speed reduction mechanism coupling the low pressure turbine section to the fan,

wherein:

- a bypass area ratio is greater than about 6.0; and
 - a ratio of an low pressure turbine section airfoil count to the bypass area ratio is less than about 170.
2. The engine of claim 1 wherein:
- the bypass area ratio is greater than about 8.0.
3. The engine of claim 1 wherein:
- the bypass area ratio is between about 8.0 and about 20.0.
4. The engine of claim 1 further comprising:
- a fan case encircling the fan blades radially outboard of the engine case.